

**Find out how to access preview-only content**  
Look inside Get Access  
Journal of Ambient Intelligence and Humanized Computing  
July 2013

# Faster and more intelligent object detection by combining OpenCL and KR

Citations  
368 Downloads 200 Citations 9 Comments

## Abstract

In this paper we present a fast implementation of a robust object detector by using OpenCL. The use of fast object detection is of great use for a broad range of applications in multiple domains. OpenCL allows for scalability to more performant and different types of hardware, with minimal changes to the implementation. By using a GPU as execution device, we exploit the data parallelism opportunities of the algorithm. We also discuss the use of knowledge representation as a means to integrate expert knowledge into applications. This can be used both for faster processing by limiting the searching space, and for applications to work more autonomous by exploiting a higher level of intelligence.

Page %P

Page 1

# Faster and more intelligent object detection by combining OpenCL and KR

Floris De Smedt · Lars Struyf · Sander Beckers ·  
Joost Vennekens · Gorik De Samblanx ·  
Toon Goedemé

Received: 27 December 2012 / Accepted: 10 June 2013  
© Springer-Verlag Berlin Heidelberg 2013

**Abstract** In this paper we present a fast implementation of a robust object detector by using OpenCL. The use of fast object detection is of great use for a broad range of applications in multiple domains. OpenCL allows for scalability to more performant and different types of hardware, with minimal changes to the implementation. By using a GPU as execution device, we exploit the data parallelism opportunities of the algorithm. We also discuss the use of knowledge representation as a means to integrate expert knowledge into applications. This can be used both for faster processing by limiting the searching space, and for applications to work more autonomous by exploiting a higher level of intelligence.

**Keywords** OpenCL · Data parallelism · Part based object detection · Knowledge representation

## 1 Introduction

Object detection has endless possibilities in many application areas of computer vision. For example the detection of humans can be used in surveillance applications,

detection of vulnerable road users (Van Beeck et al. 2011; Cho et al. 2012), blurring of persons in mobile mapping images for privacy issues, human–robot interaction, e-health applications such as the detection of falling elderly people (Willems et al. 2009), ...

It is important that the detection of the object happens as fast as possible while at the same time as accurately as possible. Many applications expect real-time performance while having a small amount of false positives. Even faster as real-time detection speeds are beneficial since this allows more processing time to be consumed by post-processing steps.

Recently, a number of state-of-the-art object detection algorithms are described in literature that have a very high recognition performance (Felzenszwalb et al. 2008, 2010a; Leibe et al. 2004; Gall et al. 2011; Dollár et al. 2009a). The downside of these powerful algorithms is that they come with a high computational cost. The algorithm we chose to implement (Felzenszwalb et al. 2010b) is a very robust algorithm based on histograms of oriented gradients proposed by Dalal and Triggs (2005). To increase performance, we implement this algorithm in OpenCL, a novel open standard for heterogeneous computing. This allows us to execute the algorithm on dedicated hardware that exploits the opportunity of data parallelism.

In Sect. 2, we give an overview of object detection and explain how the algorithm we implement works. We will also explain why a faster implementation of such a robust algorithm would be beneficial. In Sect. 3, we will discuss in detail the implementation of the construction of the feature pyramid, which is the searching space for model evaluation. In this section we handle the advantages and disadvantages of these choices and how we can circumvent the obstacles. In Sect. 4, we will discuss the experiments we have done and the timing results. In Sect. 5 we describe the

F. De Smedt (✉) · L. Struyf · S. Beckers · J. Vennekens ·  
G. De Samblanx · T. Goedemé  
Campus De Nayer, Lessius Mechelen,  
Association KU Leuven, Leuven, Belgium  
e-mail: floris.desmedt@esat.kuleuven.be

F. De Smedt · T. Goedemé  
Department of Electrical Engineering, KU Leuven,  
Leuven, Belgium

S. Beckers · J. Vennekens · G. De Samblanx  
Department of Computing Science, KU Leuven,  
Leuven, Belgium

No Body Text -- translate me!



Within this Article

1. Introduction
2. Object detection
3. Implementation
4. Experimental timing results
5. Combining of object detection with knowledge representation
6. Future work
7. Conclusion
8. References
9. References



### References (21)

1. Cho H, Rybski P, Bar-Hillel A, Zhang W (2012) Real-time pedestrian detection with deformable part models. In: IEEE intelligent vehicles symposium
2. Dalal N, Triggs B (2005) Histograms of oriented gradients for human detection. In: International conference on CVPR, vol 2, pp 886–893
3. Dollár P, Belongie S, Perona P (2010) The fastest pedestrian detector in the west. In: BMVC
4. Dollár P, Tu Z, Perona P, Belongie S (2009a) Integral channel features. In: BMVC
5. Dollár P, Wojek C, Schiele B, Perona P (2009b) Pedestrian detection: a benchmark. In: CVPR
6. Felzenszwalb P, Girschick R, McAllester D (2010a) Cascade object detection with deformable part models. In: Proceedings of the IEEE conference on CVPR
7. Felzenszwalb P, Girshick R, McAllester D (2010b) Discriminatively trained deformable part models, release 4. <http://people.cs.uchicago.edu/~pff/latent-release4/>
8. Felzenszwalb P, Girschick R, McAllester D, Ramanan D (2010c) Object detection with discriminatively trained part based models. *IEEE Trans Pattern Anal Mach Intell* 32(9):1627–1645. doi:10.1109/TPAMI.2009.167. <http://dx.doi.org/10.1109/TPAMI.2009.167>
9. Felzenszwalb P, McAllester D, Ramanan D (2008) A discriminatively trained, multiscale, deformable part model. In: Proceedings of the IEEE Conference on CVPR
10. Gall J, Yao A, Razavi N, Van Gool L, Lempitsky V (2011) Hough forests for object detection, tracking, and action recognition. *IEEE Trans Pattern Anal Mach Intell* 33(11):2188–2202. doi:10.1109/TPAMI.2011.70. <http://dx.doi.org/10.1109/TPAMI.2011.70>
11. Khronos G (2011) OpenCL—the open standard for parallel programming of heterogeneous systems. <http://www.khronos.org/opencl/>
12. Kowalski R, Sergot M (1986) A logic-based calculus of events. *New Gener Comput* 4(1):67–95 CrossRef
13. Leibe B, Leonardis A, Schiele B (2004) Combined object categorization and segmentation with an implicit shape model. In: ECCV’04 workshop on statistical learning in computer vision
14. Lifschitz V (2002) Answer set programming and plan generation. *Artif Intell* 138:39–54. <http://www.cs.utexas.edu/users/ai-lab/pub-view.php?PubID=924> CrossRef
15. Lowe DG (2004) Distinctive image features from scale-invariant keypoints. *Int J Comput Vis* 60(2):91–110. doi:10.1023/B:VISI.0000029664.99615.94. <http://dx.doi.org/10.1023/B:VISI.0000029664.99615.94>

16. PETS (2010) Pets 2010 benchmark data. <http://www.cvg.rdg.ac.uk/PETS2010/a.html>
17. Reiter R (2001) Knowledge in action: logical foundations for describing and implementing dynamical systems. MIT Press, Cambridge
18. Van Beeck K, De Smedt F, Beckers S, Struyf L, Vennekens J, De Samblanx G, Goedemé T, Tuytelaars T (2011) Towards robust automatic detection of vulnerable road users: monocular pedestrian tracking from a moving vehicle. In: Proceedings of ATINER 7th annual international conference on computer science and information systems
19. Viola P, Jones M (2001) Rapid object detection using a boosted cascade of simple features. In: Proceedings of the IEEE conference on CVPR
20. Willems J, Debarde G, Bonroy B, Vanrumste B, Goedeme T (2009) How to detect human fall in video? In: An overview. Positioning and context-awareness international conference, POCA
21. Wittocx W, Marien M, Denecker M (2008) The IDP system: a model expansion system for an extension of classical logic. In: Proceedings of the 2nd workshop on logic and search

## About this Article

---

### Title

Faster and more intelligent object detection by combining OpenCL and KR

### Journal

Journal of Ambient Intelligence and Humanized Computing

### DOI

10.1007/s12652-013-0188-5

### Print ISSN

1868-5137

### Online ISSN

1868-5145

### Publisher

Springer Berlin Heidelberg

### Additional Links

- [Register for Journal Updates](#)
- [Editorial Board](#)
- [About This Journal](#)
- [Manuscript Submission](#)

### Topics

- [Computational Intelligence](#)
- [Artificial Intelligence \(incl. Robotics\)](#)
- [Robotics and Automation](#)

- User Interfaces and Human Computer Interaction

## Keywords

- OpenCL
- Data parallelism
- Part based object detection
- Knowledge representation

## Authors

- Floris De Smedt <sup>(1)</sup> <sup>(3)</sup>
- Lars Struyf <sup>(1)</sup>
- Sander Beckers <sup>(1)</sup> <sup>(2)</sup>
- Joost Vennekens <sup>(1)</sup> <sup>(2)</sup>
- Gorik De Samblanx <sup>(1)</sup> <sup>(2)</sup>
- Toon Goedemé <sup>(1)</sup> <sup>(3)</sup>

## Author Affiliations

- 1. Campus De Nayer, Lessius Mechelen, Association KU Leuven, Leuven, Belgium
- 3. Department of Electrical Engineering, KU Leuven, Leuven, Belgium
- 2. Department of Computing Science, KU Leuven, Leuven, Belgium

Continue reading...

To view the rest of this content please follow the download PDF link above.

Check out if  
it is one of  
our over  
460 members

**And learn  
about your  
benefits**

Find out now